



152 Rollins Avenue #102
Rockville, MD 20852
800-762-9010
240-780-3309 (f)
<http://www.americanfloormats.com>

Hog Heaven Confetti Anti-Fatigue Mats

Specifications

General Information:

Surface

TYPE: 95% Post Consumer Recycled Rubber

TENSIL STRENGTH: 1000

THICKNESS: 1/8"

DUROMETER: 65

Cushion

CUSHION TYPE: Nitrile Rubber / PVC

CUSHION THICKNESS: 0.5" or 0.75"

CUSHION DENSITY: 5lbs/ft

FEATURES:

1. U.V. Stable
2. Not recommended for use in areas that are exposed to grease, oils or petroleum based solvents.
3. Textured Rubber surface for superior slip resistance
4. ASTM C1028-96 Static Coefficient of Friction: Dry = 0.92 Wet = 0.86
5. Closed-cell Nitrile / PVC cushion backing provides long lasting comfort
6. Nitrile Rubber border remains flexible for the life of the mat and will not crack or curl
7. Available in 24" and 33" widths up to 40" length
8. Cushion is permanently bonded to the Nitrile rubber top surface layer and will not delaminate like mats with a glued cushion.
9. Passes Flammability Standard DOC-FF-1-70
10. Passes ATTCC Test Method 134-1996 Electrostatic Propensity of Carpets: Maximum Voltage Negative 0.7 KV
11. Static Decay Test Method 4045 Federal Standard 101B/NFPA 99 12-4.1.3.8 (F)(3)(I) – Maximum Time Recorder: .91 sec
12. Anti-Static ANSI/ESD 57-1 1994 Protection of Electrostatic Discharge of Susceptible items: Flooring Materials